

# APEX

APEX SCIENCE & ENGINEERING CORP

( OPTOELECTRONIC DIV. )

新北市中和區新民街 112 號 4 樓      Http : [www.apexgroup.com.tw](http://www.apexgroup.com.tw)  
4F, No. 112, Shin - Min St., Chung Ho Dist., New Taipei City 235, Taiwan, R.O.C.  
Tel : 886 - 2 - 2228 - 7331      Fax : 886 - 2 - 2221 - 9105

## TAD2430RETR20C

### ROHS

## DATA SHEET

Acceptance

ISSUE	VERSION	APPROVER	CHECKER	ENGINEER
	A			



<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## Contents

1. General Specification.....	4
2. Mechanical Drawing.....	5
3. Block Diagram.....	6
4. Interface Pin Function.....	7
5. Absolute Maximum Ratings.....	8
6. Electrical Characteristics.....	9
7. Optical Characteristics.....	10
8. Timing Characteristics.....	13
9. Standard Specification for Reliability.....	15
10. Specification of Quality Assurance.....	17
11. Handling Precaution.....	26
12. Packing Method.....	26

<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

# 1. General Specification

<b>Item</b>	<b>Contents</b>	<b>Unit</b>
LCD TYPE	TFT/TRANSMISSIVE	
MODULE SIZE (W*H*T)	105.50*67.20*4.70	MM
ACTIVE SIZE (W*H)	95.04*53.856	MM
PIXEL PITCH (W*H)	0.198*0.198	MM
NUMBER OF DOTS	480*272	
DIVER IC	HX8257A	
INTERFACE TYPE	24BIT RGB	
TOP POLARIZER TYPE	ANTI-GLARE	
RECOMMEND VIEWING DIRECTION	12	O'CLOCK
GRAY SCALE INVERSION DIRECTION	6	O'CLOCK
BACKLIGHT TYPE	10-DIES WHITE LED	
TOUCH PANEL TYPE	CAPACITIVE	

Messrs.

Product Specification

Model:

TAD2430RETR20C

Rev. NO.

Issued Date.

A

Aug.04,17

# 2. Mechanical Drawing


Pin	Symbol	Device Pin Loc	Power for LED	Power for LED	Power for LED	Power Ground	Power Ground	Power Ground	Power Ground	Power Ground
1	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
2	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
3	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
4	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
5	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
6	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
7	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
8	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
9	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
10	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
11	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
12	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
13	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
14	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
15	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
16	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
17	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
18	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
19	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
20	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
21	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
22	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
23	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
24	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
25	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
26	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
27	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
28	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
29	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
30	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
31	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
32	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
33	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
34	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
35	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
36	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
37	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
38	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
39	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED
40	LED	1-LED	1-LED	2-LED	3-LED	4-LED	5-LED	6-LED	7-LED	8-LED

**NOTES:**  
 1. GENERAL TOLERANCE: ±0.2  
 2. ( ) REFERENCE DIMENSION  
 3. RECOMMENDED CUSHION ADHERENT AREA: TP V, A:1.6mm  
 4. REFERENCED DIMENSION: ( )  
 5. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS



<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

### 3. Block Diagram



<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b> <b>Aug.04,17</b>

## 4. Interface Pin Function

<b>Pin No.</b>	<b>Symbol</b>	<b>Description</b>
1	LED-	Cathode of LED backlight
2	LED+	Anode of LED backlight
3	GND	Power ground
4	VDD	Power supply
5~12	R0~R7	Red data bus
13~20	G0~G7	Green data bus
21~28	B0~B7	Blue data bus
29	GND	Power ground
30	PCLK	Clock pin of serial interface
31	DISP	Display on/off mode control
32	HSYNC	Horizontal sync signal; negative polarity
33	VSYNC	Vertical sync signal; negative polarity
34	DE	Data enable signal for RGB interface operation.
35	NC	No connect
36	GND	Power ground
37	NC	No connect
38	NC	No connect
39	NC	No connect
40	NC	No connect

### CTP PIN

<b>Pin No.</b>	<b>Symbol</b>	<b>Description</b>
1	NC	No connect.
2	NC	No connect.
3	RST	External Reset, Low is active.
4	GND	Ground electrode.
5	INT	Interrupt request to the host, or Wakeup request from the host.
6	SDA	I2C data input and output.
7	SCL	I2C clock input.
8	GND	Ground electrode.
9	GND	Ground electrode.
10	VDD	Power supply for analog voltage.

<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## 5. Absolute Maximum Ratings

<b>Parameter</b>	<b>Symbol</b>	<b>Min</b>	<b>Max</b>	<b>Unit</b>
Supply voltage for analog	VDD	-0.3	4.5	V
Supply voltage for logic	VDD	-0.3	4.5	V
Supply current (One LED)	I <sub>LED</sub>		30	mA
Operating temperature	T <sub>OP</sub>	-20	+70	°C
Storage temperature	T <sub>ST</sub>	-30	+80	°C

Note : The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.



<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## 6. Electrical Characteristics

### 6.1 Input Power

Item	Symbol	Min	Typ.	Max	Unit	Applicable terminal
Supply Voltage for Analog	VDD	3.0	3.3	3.6	V	
Supply Voltage for Logic	VDD	3.0	3.3	3.6	V	
Input Voltage	V <sub>IL</sub>	GND	-	0.3VDD	V	
	V <sub>IH</sub>	0.7 VDD	-	VDD		
Input leakage Current	I <sub>LKG</sub>	-1		1	μA	

### 6.2 Backlight Driving Conditions

Item	Symbol	Value			Unit	Remark
		Min.	Typ.	Max.		
Voltage for LED Backlight	V <sub>F</sub>	14	16	17	V	I <sub>L</sub> =40mA
Current for LED Backlight	I <sub>L</sub>		40	-	mA	
Power Consumption	P		0.64		W	
LED Life Time		30,000	50,000		Hr	Note

**Note:** Brightness to be decreased to 50% of the initial value at ambient temperature TA=25°C


<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## 7. Optical Characteristics

ITEM	SYMBOL	CONDITIONS	SPECIFICATIONS			UNIT	NOTE
			MIN	TYP.	MAX		
Luminance	L	$I_L = 40\text{mA}$	190	240	290	$\text{Cd/m}^2$	
Contrast Ratio	CR	$\theta = 0^\circ$	-	250	-		
Response Time	$T_{\text{ON}}$	$25^\circ\text{C}$	-	5	-	ms	
	$T_{\text{OFF}}$		-	15	-		
CIE Color Coordinate	Red	$X_R$	0.573	0.593	0.613		
		$Y_R$	0.338	0.358	0.378		
	Green	$X_G$	0.331	0.351	0.371		
		$Y_G$	0.545	0.565	0.585		
	Blue	$X_B$	0.123	0.143	0.163		
		$Y_B$	0.079	0.099	0.119		
	White	$X_W$	0.277	0.297	0.317		
		$Y_W$	0.292	0.312	0.332		
Viewing Angle	Hor.	$\theta_{X+}$	50	60		Degree	
		$\theta_{X-}$	50	60			
	Ver.	$\theta_{Y+}$	35	45			
		$\theta_{Y-}$	50	60			
Uniformity	Un		80			%	

Messrs.			Rev. NO.	Issued Date.
Product Specification	Model:	TAD2430RETR20C	A	Aug.04,17


**Note 1: Definition of Viewing Angle  $\theta_x$  and  $\theta_y$ :**



**Note 2: Definition of contrast ratio CR:**

$$CR = \frac{\text{Luminance of white state}}{\text{Luminance of black state}}$$

**Note 3: Definition of Response Time ( $T_r, T_f$ )**




<b>Messrs.</b>		<b>Model:</b> TAD2430RETR20C	<b>Rev. NO.</b>	<b>Issued Date.</b>
<b>Product Specification</b>			<b>A</b>	<b>Aug.04,17</b>


**Note 4: Definition of Luminance**

**①The Brightness Test Equipment Setup**

Field=2° (As measuring “black” image, field=2° is the best testing condition)




**②The Brightness Test Point Setup**



Messrs.			Rev. NO.	Issued Date.
Product Specification	Model:	TAD2430RETR20C	A	Aug.04,17

## 8. Timing Characteristics

### 8.1 Parallel RGB Timing Diagram



Messrs.

Product Specification

Model:

TAD2430RETR20C

Rev. NO.

Issued Date.

A

Aug.04,17

(480RGBx272,  $T_A=25^\circ\text{C}$ , VDDIO=1.8V to 3.6V, DVSS= 0V)

Parameter	Symbol	Spec.			Unit
		Min.	Typ.	Max.	
Clock cycle	$f_{\text{CLK}}^{(1)}$	-	9	15	MHz
Hsync cycle	1/th	-	17.14	-	KHz
Vsync cycle	1/tv	-	59.94	-	Hz
Horizontal Signal					
Horizontal cycle	th	525	525	605	CLK
Horizontal display period	thd	480	480	480	CLK
Horizontal front porch	thf	2	2	82	CLK
Horizontal pulse width	thp <sup>(2)</sup>	2	41	41	CLK
Horizontal back porch	thb <sup>(2)</sup>	2	2	41	CLK
Vertical Signal					
Vertical cycle	tv	285	286	399	H <sup>(1)</sup>
Vertical display period	tvd	272	272	272	H <sup>(1)</sup>
Vertical front porch	tvf	1	2	227	H <sup>(1)</sup>
Vertical pulse width	tvp <sup>(2)</sup>	1	10	11	H <sup>(1)</sup>
Vertical back porch	tvb <sup>(2)</sup>	1	2	11	H <sup>(1)</sup>

Note: (1) Unit: CLK=1/  $f_{\text{CLK}}$ , H= th,

(2) It is necessary to keep  $tvp+tvb=12$  and  $thp+thb=43$  in sync mode. DE mode is unnecessary to keep it.

(480RGBx240,  $T_A=25^\circ\text{C}$ , VDDIO=1.8V to 3.6V, DVSS= 0V)

Parameter	Symbol	Spec.			Unit
		Min.	Typ.	Max.	
Clock cycle	$f_{\text{CLK}}^{(1)}$	-	9.6	15	MHz
Hsync cycle	1/th	-	15.72	-	KHz
Vsync cycle	1/tv	-	60	-	Hz
Horizontal Signal					
Horizontal cycle	th	525	612	-	CLK
Horizontal display period	thd	480	480	480	CLK
Horizontal front porch	thf	2	30	-	CLK
Horizontal pulse width	thp	2	46	-	CLK
Horizontal back porch	thb	2	56	-	CLK
Vertical Signal					
Vertical cycle	tv	-	262	275	H <sup>(1)</sup>
Vertical display period	tvd	-	240	-	H <sup>(1)</sup>
Vertical front porch	tvf	1	4	-	H <sup>(1)</sup>
Vertical pulse width	tvp	1	3	-	H <sup>(1)</sup>
Vertical back porch	tvb	1	15	-	H <sup>(1)</sup>

Note: (1) Unit: CLK=1/  $f_{\text{CLK}}$ , H=th,

<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## 9. Standard Specification for Reliability

### 9.1 Standard Specification for Reliability of LCD Module

No.	Item	Description	Remarks
01	High temperature operation	The sample should be allowed to stand at 70°C for 240 hours under driving condition and then returning it to normal temperature condition, and allowing it stand for 2 hours.	Note 1 IEC60068-2-2, GB2423.2-89
02	Low temperature operation	The sample should be allowed to stand at -20°C for 240 hours under driving condition and then returning it to normal temperature condition, and allowing it stand for 2 hours.	Note2 IEC60068-2-1 GB2423.1-89
03	High temperature storage	The sample should be allowed to stand at 80°C for 240 hours under no-load condition, and then returning it to normal temperature condition, and allowing it stand for 2 hours.	IEC60068-2-2 GB2423.2-89
04	Low temperature storage	The sample should be allowed to stand at -30°C for 240 hours under no-load condition, then returning it to normal temperature condition, and allowing it stand for 2 hours.	IEC60068-2-1 GB/T2423.1-89
05	Moisture storage	The sample should be allowed to stand at 60°C,90%RH MAX for 240 hours under no-load condition, then taking it out and drying it at normal temperature for 2 hours.	IEC60068-2-1 GB/T2423.3-2006
06	Thermal shock storage	The sample should be allowed to stand the following 10 cycles : -30°C for 30 minutes → normal temperature for 5 minutes → +80°C for 30 minutes → normal temperature for 5 minutes, as one cycle.	Start with cold temperature,end with high temperature IEC60068-2-14, GB2423.22-87
07	Packing vibration	Frequency range : 10Hz ~ 55Hz Amplitude of vibration : 1.5mm Sweep time: 12 min X,Y,Z 2 hours for each direction.	IEC61000-2-6 GB/T2423.5-1995
08	Packing drop test	According to ASTM-D-5327.	IEC60068-2-32 GB/T2423.8-1995
09	Electrical Static Discharge	Air: ±4KV 150pF/330Ω 5 times	IEC61000-4-2 GB/T17626.2-1998
		Contact: ±2KV 150pF/330Ω 5 time	

- Note:1.Ts is the temperature of panel's surface.  
2.Ta is the ambient temperature of sample.  
3.Sample size for each test item is 3~5pcs.

<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## 9.2 Testing Conditions and Inspection Criteria

For the final test, the testing sample must be stored at room temperature for 24 hours. After the tests listed in Table 9.2, standard specifications for reliability will be executed in order to ensure stability.

<b>No.</b>	<b>Item</b>	<b>Test Model</b>	<b>In section Criteria</b>
01	Current Consumption	Refer To Specification	The current consumption should conform to the product specification.
02	Contrast	Refer To Specification	After the tests have been executed, the contrast must be larger than half of its initial value prior to the tests.
03	Appearance	Visual inspection	Defect free.

## 9.3 MTBF

MTBF	Functions, performance, appearance, etc. shall be free from remarkable deterioration within 50,000 hours under ordinary operating and storage conditions room temperature (25±5°C), normal humidity (50±10% RH), and in area not exposed to direct sun light.
------	---



<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## 10. Specification of Quality Assurance

This standard of Quality Assurance confirms to the quality of LCD module products supplied by APEX.

### 10.1 Quality Test

Before delivering, the supplier should conduct the following tests to confirm the quality of products.

- Electrical-Optical Characteristics: According to the individual specification to test the product.
- Appearance Characteristics: According to the individual specification to test the product.
- Reliability Characteristics: According to the definition of reliability on the specification for testing products.

### 10.2 Delivery Test

Before delivering, the supplier should conduct the delivery test.

- Test method: According to MIL-STD105E.General Inspection Level II take a single Time.
- The defects classify of AQL as following:  
Major defect: AQL = 0.65  
Minor defect: AQL = 2.5  
Total defects: AQL = 2.5

### 10.3 Non-conforming Analysis & Deal With Manners

#### 10.3.1 Non-conforming Analysis

- Purchaser should provide the data detail of non-conforming sample and the non-conforming.
- After receiving the data detail from purchaser, the analysis of non-conforming should be finished within two weeks.
- If the analysis can't be finished on time, supplier must notice purchaser 3 days in advance.

#### 10.3.2 Disposition of non-conforming

- If any product defect be found during assembling, supplier must change the good for every defect after confirmation.
- Both supplier and customer should analyze the reason and discuss the disposition of non-conforming when the reason of nonconforming is not sure.

Messrs.			
Product Specification	Model:	TAD2430RETR20C	Rev. NO.
			A
			Issued Date.
			Aug.04,17

## 10.4 Agreement items


Both parties should negotiate together when the following problems happen.

- There is any problem of standard of quality assurance, and both sides should agree that it must be modified.
- There is any argument item which does not record in the standard of quality assurance.
- Any other special problem.


## 10.5 Standard of The Product Appearance Test

### 10.5.1 Manner of appearance test

- The test must be under 20W × 2 or 40W fluorescent light, and the distance of view must be at 30±5cm.
- When test the model of transmissive product must add the reflective plate.
- The test direction is base on around 10° of vertical line.
- Temperature: 25±5°C Humidity: 60±10%RH



- Definition of area:



A: Viewing area B: Outside viewing area



<b>Messrs.</b>				
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>	<b>Issued Date.</b>
			<b>A</b>	<b>Aug.04,17</b>

### **10.5.2 Basic principle**



- When the standard can not be described, AQL will be applied.
- The sample of the lowest acceptable quality level must be negotiated by both supplier and customer when any dispute happened.
- New item must be added on time when it is necessary.

<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

## 10.6 Inspection Specification

<b>NO.</b>	<b>Item</b>	<b>Criterion</b>	<b>AQL</b>												
01	Electrical Testing	1.1 Missing vertical, horizontal segment, segment contrast defect. 1.2 Missing character, dot or icon. 1.3 Display malfunction. 1.4 No function or no display. 1.5 Current consumption exceeds product specifications. 1.6 LCD viewing angle defect. 1.7 Mixed product types. 1.8 Flicker	<b>0.65</b>												
02	Black or White spots or Bright spots or Color spots on LCD (Display only)	2.1 White and black or color spots on display $\cong 0.25\text{mm}$ , no more than Five spots. 2.2 Densely spaced: No more than three spots within 3mm.	<b>2.5</b>												
03	LCD and Touch Panel black spots, white spots, contamination (non – display)	3.1 Round type: As following drawing $\Phi = (X+Y) / 2$  <table border="1" data-bbox="821 1131 1356 1377"> <thead> <tr> <th>Size(mm)</th> <th>Acceptable Q'ty</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \cong 0.10</math></td> <td>Accept no dense</td> </tr> <tr> <td><math>0.10 &lt; \Phi \cong 0.20</math></td> <td>2</td> </tr> <tr> <td><math>0.20 &lt; \Phi \cong 0.25</math></td> <td>2</td> </tr> <tr> <td><math>0.25 &lt; \Phi \cong 0.30</math></td> <td>1</td> </tr> <tr> <td><math>0.30 &lt; \Phi</math></td> <td>0</td> </tr> </tbody> </table> <p>* Densely spaced: No more than two spots within 3mm.</p>	Size(mm)	Acceptable Q'ty	$\Phi \cong 0.10$	Accept no dense	$0.10 < \Phi \cong 0.20$	2	$0.20 < \Phi \cong 0.25$	2	$0.25 < \Phi \cong 0.30$	1	$0.30 < \Phi$	0	<b>2.5</b>
		Size(mm)	Acceptable Q'ty												
$\Phi \cong 0.10$	Accept no dense														
$0.10 < \Phi \cong 0.20$	2														
$0.20 < \Phi \cong 0.25$	2														
$0.25 < \Phi \cong 0.30$	1														
$0.30 < \Phi$	0														
3.2 Line type: (As following drawing)  <table border="1" data-bbox="726 1534 1356 1803"> <thead> <tr> <th>Length(mm)</th> <th>Width(mm)</th> <th>Acceptable Q'ty</th> </tr> </thead> <tbody> <tr> <td>---</td> <td><math>W \cong 0.02</math></td> <td>Accept no dense</td> </tr> <tr> <td><math>L \cong 3.0</math></td> <td><math>0.02 &lt; W \cong 0.05</math></td> <td rowspan="2">2</td> </tr> <tr> <td><math>L \cong 2.5</math></td> <td><math>0.03 &lt; W \cong 0.08</math></td> </tr> <tr> <td>---</td> <td><math>0.08 &lt; W</math></td> <td>Rejection</td> </tr> </tbody> </table> <p>* Densely spaced: No more than two lines within 3mm.</p>	Length(mm)	Width(mm)	Acceptable Q'ty	---	$W \cong 0.02$	Accept no dense	$L \cong 3.0$	$0.02 < W \cong 0.05$	2	$L \cong 2.5$	$0.03 < W \cong 0.08$	---	$0.08 < W$	Rejection	<b>2.5</b>
Length(mm)	Width(mm)	Acceptable Q'ty													
---	$W \cong 0.02$	Accept no dense													
$L \cong 3.0$	$0.02 < W \cong 0.05$	2													
$L \cong 2.5$	$0.03 < W \cong 0.08$														
---	$0.08 < W$	Rejection													




<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

<b>NO.</b>	<b>Item</b>	<b>Criterion</b>	<b>AQL</b>									
04	Polarizer bubbles	If bubbles are visible, judge using black spot specifications, not easy to find, must check in specify direction	Size $\Phi$ (mm)	Acceptable Q'ty								
			$\Phi \leq 0.20$	Accept no dense								
			$0.20 < \Phi \leq 0.50$	3								
			$0.50 < \Phi \leq 1.00$	2								
			$1.00 < \Phi$	0								
			Total Q'ty	3								
05	Scratches	Follow NO.3 -2 Line Type.										
06	Chipped glass	Symbols: x: Chip length    y: Chip width    z: Chip thickness k: Seal width    t: Glass thickness    a: LCD side length L: Electrode pad length	2.5									
		6.1 General glass chip: 6.1.1 Chip on panel surface and crack between panels:										
												
		<table border="1"> <thead> <tr> <th>z: Chip thickness</th> <th>y: Chip width</th> <th>x: Chip length</th> </tr> </thead> <tbody> <tr> <td><math>Z \leq 1/2t</math></td> <td>Not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> <tr> <td><math>1/2t &lt; z \leq 2t</math></td> <td>Not exceed 1/3k</td> <td><math>x \leq 1/8a</math></td> </tr> </tbody> </table>		z: Chip thickness	y: Chip width	x: Chip length	$Z \leq 1/2t$	Not over viewing area	$x \leq 1/8a$	$1/2t < z \leq 2t$	Not exceed 1/3k	$x \leq 1/8a$
		z: Chip thickness		y: Chip width	x: Chip length							
		$Z \leq 1/2t$		Not over viewing area	$x \leq 1/8a$							
		$1/2t < z \leq 2t$		Not exceed 1/3k	$x \leq 1/8a$							
		☉ Unit: mm ☉ If there are 2 or more chips, x is the total length of each chip										
		6.1.2 Corner crack:										
												
<table border="1"> <thead> <tr> <th>z: Chip thickness</th> <th>y: Chip width</th> <th>x: Chip length</th> </tr> </thead> <tbody> <tr> <td><math>Z \leq 1/2t</math></td> <td>Not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> <tr> <td><math>1/2t &lt; z \leq 2t</math></td> <td>Not exceed 1/3k</td> <td><math>x \leq 1/8a</math></td> </tr> </tbody> </table>	z: Chip thickness	y: Chip width	x: Chip length	$Z \leq 1/2t$	Not over viewing area	$x \leq 1/8a$	$1/2t < z \leq 2t$	Not exceed 1/3k	$x \leq 1/8a$			
z: Chip thickness	y: Chip width	x: Chip length										
$Z \leq 1/2t$	Not over viewing area	$x \leq 1/8a$										
$1/2t < z \leq 2t$	Not exceed 1/3k	$x \leq 1/8a$										
☉ Unit: mm ☉ If there are 2 or more chips, x is the total length of each chip												



<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b> <b>Aug.04,17</b>

<b>NO.</b>	<b>Item</b>	<b>Criterion</b>	<b>AQL</b>
08	Cracked glass	The LCD with extensive crack is not acceptable.	2.5
09	Backlight elements	9.1 Illumination source flickers when lit. 9.2 Spots or scratches that appear when lit must be judged. Using LCD spot, lines and contamination standards. 9.3 Backlight doesn't light or color is wrong.	2.5 2.5 0.65
10	Bezel	Bezel must comply with product specifications.	2.5
11	PCB、COB	11.1 COB seal may not have pinholes larger than 0.2mm or contamination. 11.2 COB seal surface may not have pinholes through to the IC. 11.3 The height of the COB should not exceed the height indicated in the assembly diagram. 11.4 There may not be more than 2mm of sealant outside the seal area on PCB. And there should be no more than three places. 11.5 Parts on PCB must be the same as on the production characteristic chart, There should be no wrong parts, missing parts or excess parts. 11.6 The jumper on the PCB should conform to the product characteristic chart.	2.5 2.5 2.5 2.5 0.65 0.65
12	FPC	12.1 FPC terminal damage $\cong$ 1/2 FPC terminal width and can not affect the function , we judge accept. 12.2 FPC alignment hole damage $\cong$ 1/2 alignment area and can not affect the function , we judge accept.	2.5 2.5
13	Soldering	13.1 No cold solder joints, missing solder connections, oxidation or icicle. 13.2 No short circuits in components on PCB or FPC.	2.5 0.65

<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>



<b>NO.</b>	<b>Item</b>	<b>Criterion</b>	<b>AQL</b>																
07	Glass crack	<p>Symbols:  x: Chip length    y: Chip width    z: Chip thickness  k: Seal width    t: Glass thickness    a: LCD side length  L: Electrode pad length</p> <p>7.2 Protrusion over terminal:  7.2.1 Chip on electrode pad:</p>  <table border="1" data-bbox="558 761 1236 907"> <tr> <td>y: Chip width</td> <td>x: Chip length</td> <td>z: Chip thickness</td> </tr> <tr> <td><math>y \leq 0.5\text{mm}</math></td> <td><math>x \leq 1/8a</math></td> <td><math>0 &lt; z \leq t</math></td> </tr> </table> <p>7.2.2  Non-conductive portion:</p>  <table border="1" data-bbox="558 1276 1236 1422"> <tr> <td>y: Chip width</td> <td>x: Chip length</td> <td>z: Chip thickness</td> </tr> <tr> <td><math>y \leq L</math></td> <td><math>x \leq 1/8a</math></td> <td><math>0 &lt; z \leq t</math></td> </tr> </table> <p>⊙ If there chipped area touches the ITO terminal, over 2/3 of the ITO must remain and be inspected according to electrode terminal specifications.  ⊙ If the product will be heat sealed by the customer, the alignment mark must not be damaged.</p> <p>7.2.3 Substrate protuberance and internal crack</p>  <table border="1" data-bbox="885 1747 1324 1892"> <tr> <td>y: width</td> <td>x: length</td> </tr> <tr> <td><math>y \leq 1/3L</math></td> <td><math>X \leq a</math></td> </tr> </table>	y: Chip width	x: Chip length	z: Chip thickness	$y \leq 0.5\text{mm}$	$x \leq 1/8a$	$0 < z \leq t$	y: Chip width	x: Chip length	z: Chip thickness	$y \leq L$	$x \leq 1/8a$	$0 < z \leq t$	y: width	x: length	$y \leq 1/3L$	$X \leq a$	2.5
y: Chip width	x: Chip length	z: Chip thickness																	
$y \leq 0.5\text{mm}$	$x \leq 1/8a$	$0 < z \leq t$																	
y: Chip width	x: Chip length	z: Chip thickness																	
$y \leq L$	$x \leq 1/8a$	$0 < z \leq t$																	
y: width	x: length																		
$y \leq 1/3L$	$X \leq a$																		

<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b>
			<b>Aug.04,17</b>

<b>NO.</b>	<b>Item</b>	<b>Criterion</b>	<b>AQL</b>												
14	Touch Panel Chipped glass	<p>Symbols:  x: Chip length    y: Chip width    z: Chip thickness  k: Seal width    t: Touch Panel Total thickness    a: LCD side length  L: Electrode pad length</p> <p>14.1 General glass chip:  14.1.1 Chip on panel surface and crack between panels:</p>  <table border="1" data-bbox="454 772 1268 974"> <tr> <td>z: Chip thickness</td> <td>y: Chip width</td> <td>x: Chip length</td> </tr> <tr> <td><math>Z \leq t</math></td> <td><math>\cong 1/2 k</math> and not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> </table> <p>⊙ Unit: mm  ⊙ If there are 2 or more chips, x is the total length of each chip</p> <p>14.1.2 Corner crack:</p>  <table border="1" data-bbox="454 1366 1268 1568"> <tr> <td>z: Chip thickness</td> <td>y: Chip width</td> <td>x: Chip length</td> </tr> <tr> <td><math>z \leq t</math></td> <td><math>\cong 1/2 k</math> and not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> </table> <p>⊙ Unit: mm  ⊙ If there are 2 or more chips, x is the total length of each chip</p>	z: Chip thickness	y: Chip width	x: Chip length	$Z \leq t$	$\cong 1/2 k$ and not over viewing area	$x \leq 1/8a$	z: Chip thickness	y: Chip width	x: Chip length	$z \leq t$	$\cong 1/2 k$ and not over viewing area	$x \leq 1/8a$	2.5
z: Chip thickness	y: Chip width	x: Chip length													
$Z \leq t$	$\cong 1/2 k$ and not over viewing area	$x \leq 1/8a$													
z: Chip thickness	y: Chip width	x: Chip length													
$z \leq t$	$\cong 1/2 k$ and not over viewing area	$x \leq 1/8a$													



<b>Messrs.</b>			
<b>Product Specification</b>	<b>Model:</b>	<b>TAD2430RETR20C</b>	<b>Rev. NO.</b>
			<b>A</b>
			<b>Issued Date.</b> <b>Aug.04,17</b>

<b>NO.</b>	<b>Item</b>	<b>Criterion</b>	<b>AQL</b>										
15	Touch Panel(Fish eye, dent and bubble on film)	<table border="1"> <thead> <tr> <th>SIZE(mm)</th> <th>Acceptable Q'ty</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.2</math></td> <td>Accept no dense</td> </tr> <tr> <td><math>0.2 &lt; D \leq 0.4</math></td> <td>5</td> </tr> <tr> <td><math>0.4 &lt; D \leq 0.5</math></td> <td>2</td> </tr> <tr> <td><math>0.5 &lt; D</math></td> <td>0</td> </tr> </tbody> </table>  	SIZE(mm)	Acceptable Q'ty	$\Phi \leq 0.2$	Accept no dense	$0.2 < D \leq 0.4$	5	$0.4 < D \leq 0.5$	2	$0.5 < D$	0	2.5
SIZE(mm)	Acceptable Q'ty												
$\Phi \leq 0.2$	Accept no dense												
$0.2 < D \leq 0.4$	5												
$0.4 < D \leq 0.5$	2												
$0.5 < D$	0												
16	Touch Panel Newton ring	Newton ring dimension $\leq 1/2$ touch panel area and not affect font and line distortion( $\leq 2.5\%$ ), it is acceptable.	2.5										
17	Touch Panel Linearity	Less than 2.5% is acceptable.	2.5										
18	LCD Ripple	Touch the touch panel, can not see the LCD ripple. Pen: R 1.0mm silicon rubber. Operation Force: 80g	2.5										
19	General appearance	<p>19.1 Pin type must match type in specification sheet.</p> <p>19.2 LCD pin loose or missing pins.</p> <p>19.3 Product packaging must the same as specified on packaging specification sheet.</p> <p>19.4 Product dimension and structure must conform to product specification sheet.</p>	<p>0.65</p> <p>0.65</p> <p>0.65</p> <p>0.65</p>										

Messrs.			
Product Specification	Model:	TAD2430RETR20C	Rev. NO.
			A
			Issued Date.
			Aug.04,17

## 11. Handling Precaution

### 11.1 Handling of LCM

- Avoid external shock.
- Don't apply excessive force on the surface.
- Liquid in LCD is hazardous substance, do not lick or swallow. When the liquid is attaching to your hand, skin, cloth, etc., wash it thoroughly and immediately.
- Don't operate it above the absolute maximum rating.
- Don't disassemble the LCM.
- The operators should wear protections whenever he/she comes into contact with the module. Never touch any of the conductive parts such as the LSI pads, the copper leads on the PCB and the interface terminals with any parts of the human body.
- The modules should be kept in antistatic bags or other containers resistant to static for storage.
- The module is coated with a film to protect the display surface, be careful when peeling off this protective film since static electricity may be generated.

### 11.2 Storage

- Store it in an ambient temperature of  $25\pm 10^{\circ}\text{C}$ , and in a relative humidity of  $50\pm 10\%\text{RH}$ . Don't expose to sunlight or fluorescent light.
- Store it in a clean environment, free from dust, active gas, and solvent.
- Store it in anti-static electricity container.
- Store it without any physical load.

### 11.3 Soldering

- Use only soldering irons with proper grounding and no leakage.
- Iron: no higher than  $280\pm 10^{\circ}\text{C}$  and less than 3 sec during hand soldering.
- Rewiring: no more than 2 times.

## 12. Packing Method

----TBD