




Approval			
Capability			
Standard	UL	IEC	
Rated Voltage	1100V	1000V	
Rated Current	350A	415A	
Wire size	0-500MCM	70-240mm ²	
T/W/End plate	36/100/-mm		
Height(mm)(NS35:7.5/NS35:15/NS32)	-/131.5/129.5mm		
Rated surge voltage/Contamination Class	8KV/3		
Stripping length	40mm		
Screw thread/Tightening torque	M10/4.0N.m/35Lb-in		
Internal cylindrical gage	B15		
Insulating Material/Inflammability class	PA/V-0		
Specification		Model	Pieces
(1)Terminal block	2P	PC 240	10
(2)Fixed bridge	3P		
	10P		
(3)Insertion bridge	2P	EB 2-36/PC	10
	3P	EB 3-36/PC	10
(4)Pick-off terminal block		AGK 10-PC150/240	10
(5)Insertion profile			
(6)End bracket		E/AL-NS32	10
		E/AL-NS35	10
(7)Hexagon screw wrench		ISS 8	
(8)Zack strip		ZB 10	

HOW TO ORDER :

			P	1		X	X	X
						Customer Request		
Series No.	No. of pole			Color				
	1	2	3	4	5	6	7	8
	Gray	Blue	Black	Green	Orange	Red	Transp-arent	Yellow
				White				

	 DEGSON ELECTRONICS CO., LTD.
 THIROANGLE PROJECTION	NAME PC 240