



SPECIFICATIONS

Electrical

Current Rating: 5A AC, DC
 Voltage Rating: 250V AC, DC
 Operating Temp.: -25°C ~ +85°C
 Insulation Resistance: 1000MΩ / min.
 Dielectric Withstanding Voltage: 1500V AC / min.
 Contact Resistance: 10mΩ / max.

Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)	
	A	B
2	5.08	10.16
3	10.16	15.24
4	15.24	20.32
5	20.32	25.40
6	25.40	30.48
7	30.48	35.56
8	35.56	40.64
9	40.64	45.72
10	45.72	50.80

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差 0 ± 0.25 .00 ± ANG ±	PART NAME 品名 5.08mm HOUSING 1X??P W/LOCKING RIBS WHITE COLOR ROHS
DWG. 製圖 Helen	SCALE 比例 參考	UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2014/8/4	PAGE 張數 1 OF 1	REV. 版本 A	PART NO. 料號 H5080-XXPYW000R