

## 60X60X20 mm

## JF0620-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0620B1UR	B	12	10.2 ~ 13.8	19.11	0.291	5500	0.19	2.28	0.20	35.9	50
JF0620-1SR	B, S			17.41	0.247	5000	0.17	2.04	0.18	32.8	
JF0620-1H	B, S			15.56	0.196	4500	0.15	1.80	0.17	29.4	
JF0620-1M	B, S			13.84	0.157	4000	0.13	1.56	0.15	26.4	
JF0620-1L	B, S			12.06	0.127	3500	0.10	1.20	0.13	23.6	
JF0620-1E	B, S			10.13	0.090	3000	0.09	1.08	0.09	20.3	
JF0620-1V	B, S			8.48	0.068	2500	0.07	0.84	0.07	17.1	
JF0620B2UR	B	24	20.4 ~ 27.6	19.11	0.291	5500	0.12	2.88	0.13	35.9	
JF0620-2S	B, S			17.41	0.247	5000	0.10	2.40	0.11	32.8	
JF0620-2H	B, S			15.56	0.196	4500	0.09	2.16	0.13	29.4	
JF0620-2M	B, S			13.84	0.157	4000	0.08	1.92	0.11	26.4	
JF0620-2L	B, S			12.06	0.127	3500	0.07	1.68	0.07	23.6	
JF0620-2E	B, S			10.13	0.090	3000	0.06	1.44	0.06	20.3	
JF0620-2V	B, S			8.48	0.068	2500	0.05	1.20	0.05	17.1	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

