


Fork Terminals

Electrolytic Copper
 Tin Plated
 Easy Entry
 P.V.C. Insulation



Part No	d2	B	L	F	H	ØD	Wire Size AWG(mm ²)	Current Rating	Insulation Color	Qty/Box	Weight/Box
KTL-002-01	3.2	5.7	22.5	6.5						3000	2.2 kg
KTL-002-02	3.7	5.7	22.5	6.5						3000	2.0 kg
KTL-002-03	3.7	6.2	22.5	6.5						3000	2.1 kg
KTL-002-04	4.3	6.4	22.5	6.5	11.0	4.0	22-16 (0.25-1.65)	19 A	Red	3000	2.1 kg
KTL-002-05	4.3	7.2	22.5	6.5						3000	2.2 kg
KTL-002-06	5.3	8.0	22.5	6.5						3000	2.2 kg
KTL-002-07	3.2	5.7	22.5	6.5						2000	1.7 kg
KTL-002-08	3.7	5.7	22.5	6.5						2000	1.6 kg
KTL-002-09	3.7	6.2	22.5	6.5						2000	1.7 kg
KTL-002-10	4.3	6.4	22.5	6.5	11.0	4.5	16-14 (1.04-2.63)	27 A	Blue	2000	1.7 kg
KTL-002-11	4.3	7.2	22.5	6.5						2000	1.8 kg
KTL-002-12	5.3	8.0	22.5	6.5						2000	1.7 kg
KTL-002-13	6.4	10.7	25.5	9.0						2000	2.3 kg
KTL-002-14	4.3	8.0	25.4	6.9	13.7	6.3	12-10 (2.63-4.62)	37 A	Yellow	1500	2.0 kg
KTL-002-15	5.3	8.0	25.4	8.0						1500	2.2 kg
KTL-002-16	3.2	7.3	26.7	7.1						1500	2.7 kg
KTL-002-17	3.7	8.2	26.7	7.5						1500	2.3 kg
KTL-002-18	4.3	8.2	26.7	7.5	13.7	6.3	12-10 (2.63-6.64)	48 A	Yellow	1000	1.9 kg
KTL-002-19	5.3	9.0	26.7	8.0						1000	1.9 kg
KTL-002-20	6.4	12.0	32.7	12.0						1000	2.5 kg

Unit = mm