



C **3510** — **XX** **S** **P** **G** **B** **0** **0** **R**

- | | | | |
|-------------------------------|--|-------------------------------|---------------------------------|
| 1. PRODUCTS:
C:Connector | 5.INSULATOR MATERIAL:
P:PBT
N:Nylon 6T(S.M.T.) | 7.INSULATOR COLOR:
B:Black | 8.PACKING STYLE:
O:No Option |
| 2.SERIES NO.:
3510 | 6.CONTACT PLATING:
G:Gold Flash | 9.FILL IT WITH*
0 | 10.R:ROHS |
| 3.CONTACT NO.:
10-64 | | | |
| 4.CONTACT TYPE:
S:Straight | | | |

MATERIAL

Contact Pin : Brass
Housing : PBT . UL94V-0

SPECIFICATION

Current Rate : 3 AMP
Insulation Resistance : 5000MΩMin. at DC 500V
Contact Resistance : 20mΩMax. at DC 100mA
Dielectric Voltage : AC 500V for one minute
Operation Temperature : -40°C to + 105°C

POLES	DIM A	DIM B	DIM C
6	15.20	12.80	5.08
8	17.78	15.48	7.62
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
24	38.08	35.88	27.94
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.80	48.58	40.64
40	58.40	56.20	48.26
44	63.48	61.28	53.34
50	71.10	68.90	60.96
56	78.72	76.52	68.58
60	83.80	81.60	73.66
64	88.88	86.68	78.74

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 參考	TOLERANCE .0 =±.30 .00 =±.20 .000 =±.XXX .0000=±. ANG.=±3°
DWG. 製圖 BETTY	UNIT 單位 MM	SIZE. 紙張尺寸 A 4
DATE 制表日 2009/02/26	PAGE 張數 1 OF 1	REV. 版次 A
PART NAME 品名 BOX HEADER 2.54mm X 2.54mm XXP STRAIGHT TYPE GOLD FLASH PLATING BLACK INSULATOR PBT MATERIAL ROHS		PART NO. 料號 C3510-XXSPGB00R